

## CLEANING AND MAINTENANCE PRODUCTS

<b>DETERSOAP</b>	Soap for standard wood care. Concentrated high-gloss cleaner for oiled, varnished, waxed surfaces. DETERSOAP is a concentrated sanitising and cleansing solution for cleaning glossy treated floors. For all materials (terracotta and stone) and timber treated with waxes, oils and varnishes. <b>PERFORMANCE:</b> the active ingredients contained in the formula guarantee a sanitising and cleansing action while maintaining the treatment's original gloss over time.
<b>CLEANWAX</b> NEUTRAL TEAK WHITE BLACK	Wax for special wood care. Wax emulsion for preservation of oiled or varnished wood. CLEANWAX is an O/W emulsion containing natural waxes and resins. Wood care product for oiled and varnished surfaces indoors (parquet - furniture - panelling). <b>PERFORMANCE:</b> revives and maintains the protective and aesthetic characteristics of the initial treatment without peeling or wax build-ups. The dry residue that forms the protective layer on the material is non-toxic. No toxic or noxious components released. Self-polishing and repolishable. Yield: 1 lt / 30-40 sqm.
<b>VENETOWAX</b> FOR OILED VENETO ONLY	VENETOWAX is an O/A emulsion of natural wax and resins. Used to maintain oiled wooden surfaces (parquet - furniture - cladding). <b>USE:</b> renews and preserves over time the protective and aesthetic characteristics of the initial treatment without causing film to peel or wax to build up. The dry residue that protects the material is non-toxic; it does not release toxic or harmful substances into the environment. It is self-polishing and can be re-polished. Yield: 1 lt / 30-40 sqm.
<b>LIGNOLUX</b> (EX VELUX)	Solvent solution of mineral and vegetable waxes, for the maintenance of wood treated with oil and wax. Cleaning agent for heavily soiled impregnated surfaces or surfaces treated with oils impregnating; forms a very thin, protective wax film. Yield: 1 lt / 30-40 sqm.
<b>PULITORE</b> INTENSIVO	Concentrated sanitising cleaner for special cleaning. For all treated wooden surfaces. PULITORE INTENSIVO concentrated, water-based detergent solution containing glycols, alcohols, amines, dispersants, sequestrants, anionic and non-ionic surface active agents, and sanitising agents. All materials (terracotta and stone) and timber treated with waxes, oils and varnishes. <b>PERFORMANCE:</b> universal cleaner for special cleansing of oiled and waxed wood, with a wide range of applications depending on the degree of dilution with water. Low-foam detergent. Leaves a pleasant fragrance in the room.
<b>HYDROREP</b> NEUTRAL WHITE	Waterproofing for floors that have been treated with oil or with a "nature" finish (oiled and varnished). HYDROREP is a spray of waterproof waxes for intensive maintenance of frequently used wooden floors, varnished (solvent or water based), oiled and waxed, and for the extraordinary maintenance of spoiled and/or scratched floors. Hydrorep is also suitable for use on earthenware tiles and stone-based materials for interior decor. The product gives the surface a pleasant natural effect and makes it waterproof. Its special formula renews, maintains, protects and restores spoiled and/or scratched floors. Quantity 0.5 litre cottle. Yield: 1 lt / 30-40 sqm.
<b>DOES NOT ALTER THE NATURAL MATT FINISH</b>	
<b>KIT DI MANUTENZIONE</b>	The kit contains: a Detersoap bottle, a Cleanwax bottle, a NATUROIL pack, a woollen cloth and a sponge for polishing.
<b>BIOTOP</b> FOR OILED SURFACES ONLY	Water-based dirt- and stain-proof finishing treatment for wooden materials. B/OTOP O/W emulsion containing vegetable wax, paraffin, fatty acid ester, and non-ionic surface-active resin. <b>FIELDS OF USE:</b> all kinds of wooden surfaces indoors (flooring, furniture, structural members). <b>PERFORMANCE:</b> specific finishing treatment for oil/wax-based wood primers. With this water-repellent, stain-proof and dirt-resistant treatment, wooden surfaces are easy to clean and revive, making light work of maintenance, especially on floors. Repolishable and easy to clean. It does not form films or glossy layers. Natural-looking wood finish guaranteed. Formulated in water. No unpleasant odours left. The product's non-volatile residual components are not specifically toxic. No toxic or noxious components released. Yield: 1 lt / 30-40 sqm.
<b>NATUROIL</b>	Ready-to-use repair oil for oiled wooden floors. NATUROIL is an oil for the special care and restoration of areas that have become fatigued or damaged by wear. <b>PERFORMANCE:</b> it nourishes the wood and restores the surface protection, making the priming treatment last longer. Yield: 1 lt / 30-40 sqm.
<b>OIL-WAX PRIMER FOR USE ON WOOD</b>	Oil-wax primer for use on wood installed outdoors. For application to all pre-oiled or untreated outdoor surfaces. <b>Function:</b> Water-repellent primer which forms a protective oil-wax coat resistant to weather and easily restored with no need to re-sand the wood. <b>Coverage:</b> - On absorbent or coarse-grain wood: 1 lt / 8-10 sqm. - On unabsorbent and oily wood (teak/iroko): 1 lt / 15-20 sqm.

## THERMO-ACOUSTIC LAYER \*

### CP "HD" PAD

HOPO high density polyethylene insulating pad backed with a PE film anti moisture barrier. Supplied with adhesive edges to attach and seal.  
2mm thick  
SD = 100m  
RWS 2 (22 sone)  
15/sqm rolls (1m x 15m)

### CP "S" PAD

NPE polyethylene insulating pad, backed with an aluminium anti moisture barrier. Supplied with adhesive edges to attach and seal.  
2mm thick  
SD = 180m  
RWS 0 (30 sone)  
15/sqm rolls (1m x 15m)

### CP "N" PAD

Low heat resistance HOPO polyethylene insulating pad suitable for use with under-floor heating.  
1mm thick  
Rt = 0.032 m2K/W  
SD = 12m  
RWS 2 (23 sone)  
20/sqm rolls (1m x 20m)

### CP "K" PAD

Soundproof insulating pad made of chemical-free vegetable fibres. Suitable when high performance, sustainability (renewable raw materials), and environmental compatibility are required. This product cannot be attacked by insects and is resistant to mould and fully recyclable.  
3mm thick  
SD = 7m  
RWS 1 (30 sone)  
20/sqm rolls (1m x 20m)

\* Freight costs for the thermo-acoustic layer will be charged to the customer if it is ordered separately

## GLUE

### ADESIVIL D3

Water-resist vinyl adhesive for prefinished wood floating floors. Pack of 0.5 kgs. Coverage: 15m<sup>2</sup> per pack.

### 2K

CATAL. 9-1  
WITH 2K COMP. B ADHESIVE

Bicomponent epoxy polyurethane adhesive (9-1), odourless, without solvents or water, for gluing traditional wooden floorboards of all sizes, pre-finished (pre-varnished) on waterproof concrete sub-floors and existing non-absorbant floors (ceramic, gres, marble, etc.). Also suitable for laying on sub-floors with radiant heating systems, it is exceptionally adhesive. Available in the shades oak and walnut. 10 (9+1) kgs tin. Yield: 1300/1900 g/ sqm.